



Production Car Care Products
Office (209) 943-7337
www.msdsatproduction.com

SAFETY DATA SHEET

FILE NO.: 107 SDS DATE: August 24, 2018

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Satin Black Engine Paint
SYNONYMS: N/A
PRODUCT CODES:

MANUFACTURER: Production Car Care Products
DIVISION: N/A
ADDRESS: 1000 East Channel Street
Stockton, CA 95205

EMERGENCY PHONE: CANUTEC: (613) 996-6666
CHEMTREC PHONE: (800) 424-9300
OTHER CALLS: Office (209) 943-7337
FAX PHONE: (209) 943-7337

SECTION 1 NOTES:

SECTION 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:
ROUTES OF ENTRY: N/A

POTENTIAL HEALTH EFFECTS

EYES: Irritation, redness, tearing, blurred vision, corneal burns.

SKIN: Irritation, drying, cracking, defatting, dermatitis.

INGESTION: Irritation, nausea, vomiting, diarrhea, death.

INHALATION: Nasal, respiratory irritation, dizziness, fatigue, nausea, headache, asphyxiation.

ACUTE HEALTH HAZARDS: Eyes: Irritation, redness, tearing, blurred vision, corneal burns. Skin: Irritation, drying, cracking, defatting, dermatitis. Breathing: Nasal, respiratory irritation, dizziness, fatigue, nausea, headache. Ingestion: Irritation, nausea, vomiting, diarrhea.

CHRONIC HEALTH HAZARDS: Asphyxiation & death.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Poor General Health.





CARCINOGENICITY

OSHA: 300, 300, 100 ppm, 200, 100

ACGIH: 300, 300, 100 ppm, 200, 100

NTP: N/L

IARC: N/L

OTHER: N/A

SECTION 2 NOTES: N/A.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT:

Light Petroleum Naphtha

VM & P Naphtha

Rule 66 Mineral Spirits

*Toluene

*Xylene

CAS NO.

64742-89-8

8030-30-6

64742-88-7

108-88-3

1330-20-7

% WT

N/A

N/A

N/A

N/A

N/A

SARA 313 REPORTABLE

N/A

N/A

N/A

N/A

N/A

OSHA PEL:

300 ppm

300 ppm

100 ppm

200 ppm

100 ppm

ACGIH TLV

300 ppm

300 ppm

100 ppm

200 ppm

100 ppm

NTP

N/A

N/A

N/A

N/A

N/A

IARC

N/A

N/A

N/A

N/A

N/A

N/A

OSHA 1910 (Z)

N/A

N/A

N/A

N/A

N/A

N/A

EHS

N/A

N/A

N/A

N/A

N/A

LD50

(Oral)

N/A

N/A

N/A

rat-6700 ppm/4H

LC50

(Inhalation)

N/A

N/A

N/A

mouse-5320 ppm/8H

rat-5000 mg/kg

SECTION 3 NOTE: N/A.

SECTION 4: FIRST AID MEASURES

EYES: Eyes: Flush with large quantities of water lifting upper and lower lid.

SKIN: Wash with soap and water after removing contaminated clothing.

INGESTION: Do not induce vomiting. Aspiration of Xylene in lungs can cause fatal pneumonitis.

INHALATION: Remove to fresh air. If necessary give oxygen and/or artificial respiration.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS: N/A

SECTION 4 NOTES: N/A.

SECTION 5: FIRE-FIGHTING MEASURES

METHOD USED:

FLASH POINT: 60 °F (TCC)

AUTO IGNITION TEMPERATURE: N/D

EXTINGUISHING MEDIA: Regular Foam, Carbon Dioxide, or Dry Chemical.

SPECIAL FIRE FIGHTING PROCEDURES: Use self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Residue may ignite - Vapor may travel.

SECTION 5 NOTES: N/A

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES: Avoid using in closed area. Absorb with sand or absorbent material and prevent runoff to sewer or surface water.

SECTION 6 NOTES: N/A

SECTION 7: HANDLING AND STORAGE

HANDLING AND STORAGE: Keep out of reach of children - Handle as a flammable liquid.

OTHER PRECAUTIONS: N/A.

SECTION 7 NOTES: N/A

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: N/A.

VENTILATION: Avoid using in closed area.

RESPIRATORY PROTECTION: Should wear if OSHA PEL/TLV is exceeded NIOSH/MSHA or other recognized approved air-supplied respirator.

EYE PROTECTION: Safety spectacles.

SKIN PROTECTION: Protective gloves required.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Respiratory equipment.

WORK HYGIENIC PRACTICES: No eating, drinking or smoking. Wash up after.

EXPOSURE GUIDELINES: N/A

SECTION 8 NOTES: N/A.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Thick black liquid.

ODOR: Petroleum-like odor.

PHYSICAL STATE: Liquid.

pH AS SUPPLIED: N/D

pH (Other):

BOILING POINT: N/D

F:

C:

MELTING POINT: N/D

F:

C:

FREEZING POINT: N/D

F:

C:

VAPOR PRESSURE (mmHg): N/D

@

F:

C:

VAPOR DENSITY (AIR = 1): N/D

@

F:

C:

SPECIFIC GRAVITY: (H₂O = 1)

@ N/D

F:

C:

EVAPORATION RATE: (Butyl Acetate = 1)

BASIS (=1): N/D

SOLUBILITY IN WATER: Not soluble.

SECTION 10: STABILITY AND REACTIVITY

STABLE
X

UNSTABLE

STABILITY: Stable

CONDITIONS TO AVOID (STABILITY): N/A.

INCOMPATIBILITY (MATERIAL TO AVOID): Carbon Dioxide, Carbon Monoxide, and possible Acrolein.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Strong Oxidizing Agents.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID (POLYMERIZATION): Heat or Flame.

SECTION 10 NOTES: N/A

SECTION 11: TOXICOLOGICAL INFORMATION

OVER EXPOSURE: Irritation - Nausea.

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: Product is a mixture of listed components.

SECTION 12 NOTES: N/A

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: In accordance with Local, State and federal regulations.

RCRA HAZARD CLASS: N/D

SECTION 14: TRANSPORT INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION

PROPER SHIPPING NAME: Paint Related Material, 3, UN 1263, PG II

HAZARD CLASS:

ID NUMBER:

PACKING GROUP:

LABEL STATEMENT:

WATER TRANSPORTATION

PROPER SHIPPING NAME:

HAZARD CLASS:

ID NUMBER:

PACKING GROUP:

LABEL STATEMENTS:

AIR TRANSPORTATION

PROPER SHIPPING NAME:

HAZARD CLASS:

ID NUMBER:

PACKING GROUP:

LABEL STATEMENTS:

OTHER AGENCIES:

SECTION 14 NOTES:

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

TSCA (TOXIC SUBSTANCE CONTROL ACT):

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT):

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT):

311/312 HAZARD CATEGORIES:

313 REPORTABLE INGREDIENTS:

STATE REGULATIONS:

INTERNATIONAL REGULATIONS:

SECTION 15 NOTES:

SECTION 16: OTHER INFORMATION

OTHER INFORMATION:

PREPARATION INFORMATION:

DISCLAIMER: The information contained herein is based on data considered accurate. However, the information is provided without any warranty, expressed or implied, regarding its correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility for personal injury or property damage to vendees, users or third parties caused by the material. We also do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.