



Production Car Care Products

Office (209) 943-7337

www.msdsatproduction.com

SAFETY DATA SHEET

FILE NO.: 129 SDS DATE: August 24, 2018

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Transparent Clear Aerosol Paint
SYNONYMS: N/A
PRODUCT CODES:

MANUFACTURER: Production Car Care Products
DIVISION: N/A
ADDRESS: 1000 East Channel Street
Stockton, CA 95205

EMERGENCY PHONE: CANUTEC: (613) 996-6666
CHEMTREC PHONE: (800) 424-9300
OTHER CALLS: Office (209) 943-7337
FAX PHONE: (209) 943-7337

SECTION 1 NOTES:

SECTION 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:
ROUTES OF ENTRY: N/A

POTENTIAL HEALTH EFFECTS

EYES: Causes eye and skin irritation.

SKIN: Causes eye and skin irritation.

INGESTION: Can cause stomach and/or intestinal irritation, nausea, vomiting, diarrhea. Aspiration of vomitus can cause chemical pneumonitis, which can be fatal. METHYLENE CHLORIDE is metabolized by the body to carbon monoxide which reduces the blood's oxygen carrying capacity. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Prolonged and repeated breathing of spray mist and/or sanding dust over a period of years may cause dust disease of the lungs. NTP has classified METHYLENE CHLORIDE as a carcinogenic in rats and mice at high levels of exposure to vapors throughout their lifetime. The U.S. Consumer Product Safety Commission considers METHYLENE CHLORIDE to be a probable human carcinogen. ACGIH lists METHYLENE CHLORIDE as a suspect human carcinogen. METHYLENE CHLORIDE is known to the state of California to cause cancer. Risk depends on duration and level of exposure.

INHALATION: Irritation of the respiratory; may affect the brain or nervous system causing dizziness, headache, nausea, weakness and fatigue. Extreme exposure can result in unconsciousness and even respiratory arrest.

ACUTE HEALTH HAZARDS: EYES: Causes eye and skin irritation. SKIN: Causes eye and skin irritation. INGESTION: Can cause stomach and/or intestinal irritation, nausea, vomiting, diarrhea. Aspiration of vomitus can cause chemical pneumonitis, which can be fatal. METHYLENE CHLORIDE is metabolized by the body to carbon monoxide which reduces the blood's oxygen carrying capacity. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Prolonged and repeated breathing of spray mist and/or sanding dust over a period of years may cause dust disease of the lungs. NTP has classified METHYLENE CHLORIDE as a carcinogenic in rats and mice at high levels of exposure to vapors throughout their lifetime. The U.S. Consumer Product Safety Commission considers METHYLENE CHLORIDE to be a probable human carcinogen. ACGIH lists METHYLENE

CHLORIDE as a suspect human carcinogen. METHYLENE CHLORIDE is known to the state of California to cause cancer. Risk depends on duration and level of exposure.

CHRONIC HEALTH HAZARDS: permanent brain and nervous system damage.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: None when used in accordance with Section X Control Measures.



CARCINOGENICITY

OSHA: 2 mg/m³ (ceiling), 25 ppm (skin)

ACGIH: 2 mg/m³ (ceiling), 25 ppm (skin)

NTP: N/L

IARC: N/L

OTHER: N/A

SECTION 2 NOTES: N/A.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT:

Toluene
Methylene Chloride
Propane/Isobutane

CAS NO.

108-88-3
75-09-2
74-98-6/75-28-5

% WT

37
30
25

SARA 313 REPORTABLE

N/A
N/A
N/A

OSHA PEL:

150 ppm or 560 mg/M³
500 ppm or 2000 mg/M³
N/A

ACGIH TLV

150 ppm or 560 mg/M³
500 ppm or 2000 mg/M³
N/A

NTP

N/A
N/A
N/A

<u>IARC</u>	<u>OSHA 1910 (Z)</u>	<u>EHS</u>
N/A	N/A	N/A
N/A	N/A	N/A
N/A	N/A	N/A
<u>LD50</u> (oral-rat) 5000 mg/kg	<u>LC50</u> (inhalation-mouse) 5320 ppm/8H	
N/A	N/A	
N/A	N/A	

SECTION 3 NOTE: [01] See Section V for carcinogenicity information.
 [02] ACGIH simple asphyxiant, Vapor pressure = 208 P SIG @ 100 °F
 Hazardous according to: a-SARA 302/304, b SARA 313, c-CERCLA 103 (a) *Vapor Pressure =mm Hg

SECTION 4: FIRST AID MEASURES

EYES: Flush with water for 15 minutes.

SKIN: Remove contaminated clothing, wash with soap and water. Get medical attention if irritation persists. Warning: Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

INGESTION: Do not induce vomiting. Aspiration of vomitus can cause chemical pneumonitis which can be fatal.

INHALATION: Remove to fresh air, if necessary administer oxygen and/or artificial respiration.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS: N/A

SECTION 4 NOTES: N/A.

SECTION 5: FIRE-FIGHTING MEASURES

METHOD USED:

FLASH POINT: -156 °F Setflash.

AUTO IGNITION TEMPERATURE: N/D

EXTINGUISHING MEDIA: Regular Foam, Carbon Dioxide or Dry Chemical or other NFPA approved method for treating Class B fire.

SPECIAL FIRE FIGHTING PROCEDURES: Use full protective equipment including self-contained breathing apparatus. Water spray may be ineffective. If water is used, fog nozzles are preferable.

If exposed to fire or extreme heat, water should be used to cool closed containers and prevent pressure build-up or possible auto-ignition.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep container tightly closed. Isolate from heat & flame. Due to pressure build-up, closed containers exposed to extreme heat may explode. Never use a welding or cutting torch on or near container (even empty) as product or its residue may ignite. During emergency conditions, overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SECTION 5 NOTES: N/A

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES: Absorb with sand or absorbent material, Prevent runoff to sewer or surface water.

SECTION 6 NOTES: N/A

SECTION 7: HANDLING AND STORAGE

HANDLING AND STORAGE: Keep away from heat, sparks, and flame. Do not smoke. Extinguish all pilot lights and turn off all sources of ignition including heaters, fans and other non-explosion-proof electrical equipment, during use and until all vapors are gone. Vapors may ignite explosively or cause flash fire. Vapors may spread long distances and beyond closed doors. Prevent build-up of vapors by maintaining continuous flow of fresh air. **DANGER:** Extremely flammable liquid and vapor. Contents under pressure. Exposure to heat or prolonged exposure to sun may cause bursting. Do not puncture, incinerate (burn) or store above 120 °F. Do not place in garbage compactors. Do not store above 120 °F or near fire or open flame. Store large quantities in building designed to comply with OSHA 1910.106. Keep container closed when not in use. Do not transfer contents to bottles or other unlabeled containers. Do not reuse empty containers. Keep out of reach of children. Pending government agencies review, it is recommended that individual exposure to Methylene Chloride, including short term concentration peaks, be reduced to the lowest levels feasible by utilizing good industrial hygiene practices.

OTHER PRECAUTIONS: Warning: This product contains a chemical known to the state of California to cause cancer, birth defects or other reproductive harm.

SECTION 7 NOTES: N/A

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: N/A.

VENTILATION: Avoid using in closed area.

RESPIRATORY PROTECTION: Should wear if OSHA PEL/TLV is exceeded NIOSH/MSHA or other recognized approved air-supplied respirator.

EYE PROTECTION: Safety spectacles.

SKIN PROTECTION: Protective gloves required.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Do not get on skin. Solvent impermeable clothing and boots to prevent contact are recommended.

WORK HYGIENIC PRACTICES: No eating, drinking or smoking. Wash up after.

EXPOSURE GUIDELINES: N/A

SECTION 8 NOTES: N/A.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Product is a thin Liquid with Purplish Color.

ODOR: Lemon-like odor.

PHYSICAL STATE: Liquid.

pH AS SUPPLIED: 9-10

pH (Other):

BOILING POINT: N/D

F: 42-232°F

C: 5.5 – 111.11°C

MELTING POINT: N/D

F:

C:

FREEZING POINT: N/D

F:

C:

VAPOR PRESSURE (mmHg): N/D

@

F:

C:

VAPOR DENSITY (AIR = 1): N/D
@ Heavier than air

F:
C:
SPECIFIC GRAVITY: (H2O = 1)
@ 1.024

F:
C:
EVAPORATION RATE: (Butyl Acetate = 1)
Faster than ether.

BASIS (=1): N/D

SOLUBILITY IN WATER: N/L.

SECTION 10: STABILITY AND REACTIVITY

STABLE
X

UNSTABLE

STABILITY: Stable

CONDITIONS TO AVOID (STABILITY): Heat, Sparks and Flame.

INCOMPATIBILITY (MATERIAL TO AVOID): Strong Oxidizing Agents.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Carbon dioxide, carbon monoxide and various hydrocarbons.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID (POLYMERIZATION): Heat or flame.

SECTION 10 NOTES: N/A

SECTION 11: TOXICOLOGICAL INFORMATION

OVER EXPOSURE: None when used in accordance with Safe Handling and Use Information.

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: Product is a mixture of listed components.

SECTION 12 NOTES: N/A

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: In accordance with Local, State and federal regulations.

RCRA HAZARD CLASS: N/D

SECTION 14: TRANSPORT INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION
PROPER SHIPPING NAME: Paint Related Material, 3, UN 1263, PG III
HAZARD CLASS:
ID NUMBER:
PACKING GROUP:
LABEL STATEMENT:

WATER TRANSPORTATION
PROPER SHIPPING NAME:
HAZARD CLASS:
ID NUMBER:

**PACKING GROUP:
LABEL STATEMENTS:**

**AIR TRANSPORTATION
PROPER SHIPPING NAME:
HAZARD CLASS:
ID NUMBER:
PACKING GROUP:
LABEL STATEMENTS:**

OTHER AGENCIES:

SECTION 14 NOTES:

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

TSCA (TOXIC SUBSTANCE CONTROL ACT):

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT):

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT):

311/312 HAZARD CATEGORIES:

313 REPORTABLE INGREDIENTS:

STATE REGULATIONS:

INTERNATIONAL REGULATIONS:

SECTION 15 NOTES:

SECTION 16: OTHER INFORMATION

OTHER INFORMATION:

PREPARATION INFORMATION:

DISCLAIMER: The information contained herein is based on data considered accurate. However, the information is provided without any warranty, expressed or implied, regarding its correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility for personal injury or property damage to vendees, users or third parties caused by the material. We also do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.