



SAFETY DATA SHEET

Issuing Date: 29-OCT-2019

Revision Date: 5-NOV-2019

Version 1

1. IDENTIFICATION

Product Name Truckers Choice/Metal Plus Metal Polish
Product ID: TCMP-16
Product Type: Finished Product
Recommended Use Metal Polish

**Supplier/
Distributor** Truckers Choice Products
 5600 Caleb Road
 Fallon, NV 89406

E-mail Address info@truckerschoice@mindspring.com

Emergency Telephone (800) 443-5347
 CANUTEC: (613)996-6666
 CHEMTREC - 1-800-424-9300


2. HAZARD IDENTIFICATION

Classification



CONSUMING, INGESTING, INHALING or INCORRECT HANDLING or USE of chemicals can expose you to chemicals which can cause irreversible eye/skin/inhalation/cancer damage. Wash & rinse hands with fresh water after using. Read M/SDS BEFORE USING

WORKER/USER PROTECTION RECOMMENDATIONS
 ALWAYS USE SAFETY GOGGLES AND RUBBER GLOVES AND WORK IN WELL VENTILATED AREAS WHEN USING OR HANDLING CHEMICALS



HAZARD RATING IDENTIFICATION

Concentrate		In Dilution		HAZARD RATING
1	Flammability	1		
1	Health	1		3 = High
0	Reactivity	0		2 = Moderate
0	Special Hazard	0		1 = Slight
				0 = Insignificant

WARNING: READ MSDS BEFORE USING WWW.MSDSATPRODUCTION.COM



2.2 Label Elements

Hazard Statements – Physical

Combustible liquid

Hazardous Statements – Health

May be fatal if swallowed and enters airways

Precautionary Statement Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements – Response

IF SWALLOWED: Immediately call a POISON CENTER or doctor

Precautionary Statements - Storage

Store locked up

Precautionary Statements – Disposal

Dispose of contents/container to disposal recycling center. Waste management should be in full compliance with federal, state and local laws.

Hazards not otherwise classified (HNOC) none

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Synonyms	Trade Secret	CAS-No	Weight %
MINERAL SEAL OIL	-	No	0064742-46-7	85 - 100

4. FIRST AID MEASURES

First aid measures for different exposure routes

Eye contact

Remove Source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for 15-20 minutes while holding the eyelids open. Remove contact lenses. If present and easy to do. Continue rinsing. Take care not to rinse contaminated water into the unaffected eye or onto the face. Get immediate medical attention.

Inhalation

The inhalation of vapors or aerosols may be irritating for the respiratory tract and for mucous membranes. Vapors Inhaled in strong concentration have narcotic effect on the central nervous system.
Remove source of exposure or move person to fresh air and keep comfortable for breathing. If victim is not breathing. Call 911 and administer CPR as directed
Eliminate all ignition sources if safe to do so

Skin contact

Remove contaminated clothing and shoes. Wash before re-use.
Rinse/wash with lukewarm, gently flowing water (and mild soap) for 15-20 minutes or until product is removed.
If skin irritation occurs or you feel unwell: Get medical advice/attention

Ingestion

If swallowed accidentally, the product may enter the lungs due to its low viscosity and lead to the rapid development of Very serious pulmonary lesions (medical survey during 48hours). Ingestion may cause gastrointestinal irritation, nausea, Vomiting and diarrhea. Do NOT induce vomiting. If vomiting occurs naturally, lie on your side, in the recovery position. Immediately call 911 POISON CENTER/doctor. Immediately transport to the nearest medical facility for treatment

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	Dry chemical, CO ₂ , or fog is recommended. Water spray is recommend to cool or protect exposed materials or structures. CO ₂ can displace oxygen. Use caution when applying carbon dioxide in confined spaces, simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam. Sand or earth may be used for small fires only.
Unsuitable Extinguishing Media	Do NOT use a solid stream of water as it may scatter and spread the fire.
Specific Hazards in Case of Fire	No Information Available
Fire- fighting Procedures	Isolate Immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.
Special protective Actions	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Emergency Procedure

ELIMINATE all ignition sources (no Smoking, flares, sparks or flames in immediate area).

RELEASE CAN CAUSE FIRE/EXPLOSION, LIQUIDS / VAPORS MAY IGNITE.

Do not touch or walk through spilled material

Isolate hazard area and keep unnecessary people away. Remove all possible sources of ignition in the surrounding area.

Authorities if any exposure to the general public or the environment occurs or is likely to occur.

If spilled material is cleaned up using a regulated solvent, the resulting waste mixture may be regulated.

Recommended Equipment

Positive pressure, full-face piece self-contained breathing apparatus (SCBA), or positive pressure supplied air respirator
With escape SCBA (NIOSH approved).

Personal Precautions

Avoid breathing vapor. Avoid contact with skin, eye or clothing. Eliminate all ignition sources (no smoking, flares sparks or Flames in immediate area). Use explosive proof equipment. Avoid inhalation of dust and contact with skin and eyes. Do Not touch damaged containers or spilled materials unless wearing appropriate protective clothing

Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, and other unauthorized drainage system and natural waterways by using sand, earth, or other appropriate barriers.

Methods and Materials for Containment and Cleaning up

Sand, clay and absorbent socks can be used to contain a spill

Recommended to control emissions near the source.

Storage Room Requirements

MATERIALS TO AVAOID: Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty container retain residue and may be dangerous.

Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored.

Ground and bound containers and receiving equipment. Avoid static electricity by grounding.

Electrostatic charges may be generated during pumping. Keep away from aerosols, flammables, oxidizing agents, corrosives and from other flammable products.

7. HANDLING AND STORAGE

General

- Wash hands after use.
- Do not get in eyes, on skin or on clothing.
- Do not breathe vapors or mists.
- Use good personal hygiene practices.
- Eating, drinking and smoking in work areas is prohibited.
- Remove contaminated clothing and protective equipment before entering eating areas.
- Eyewash stations and showers should be available in areas where this material is used and stored.

Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory Protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers.

Skin Protection

Use of glove approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, and dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over- boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

Eye Protection

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working With liquids. If additional protection is needed for entire face, use in combination with a face shield.

Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit

Chemical Name	CAS-No	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA Tables (Z1, Z2,Z3)
MINERAL SEAL OIL	0064742-46-7	500	2000	1

9. PHYSICAL AND CHEMICAL PROPERTIES

Note Chemical Nature: A complex and variable combination of paraffinic and cyclic hydrocarbons having a carbon number range Predominantly of C13 to C23 and boiling in the range of approximately 210 Deg. C to 370 Deg. C

Physical and Chemical Properties

Specific Gravity	0.82
Density	6.84 lb /gal
% VOC	100.00%
Density VOC	6.84 lb/gal
% Solids by Weight	0.00%
Appearance	Colorless liquid
Odor Threshold	N/A
Odor Description	Hydrocarbon-like
pH	N/A
Water Solubility	N/A
Flammability	C
Flash Point Symbol	>93 C
Viscosity	N/A
Lower Explosion Level	N/A
Vapor Pressure	N/A
Vapor Density	N/A
Freezing Point	N/A
Melting Point	N/A
Low Boiling Point	N/A
High Boiling Point	N/A
Auto Ignition Temp	213 C
Decomposition Pt	N/A
Evaporation Rate	N/A
Coefficient Water/Oil	N/A
VOC Composite Partial Pressure	0.0013 mmHg

10. STABILITY AND REACTIVITY

Stability

Stable under normal conditions of use.

Conditions to Avoid

Avoid heat, sparks, open flames and other ignition sources.

Hazardous Reactions/Polymerization

No data available

Incompatible Materials

Oxidizing agents
Strong acids
Strong oxidizing agents

Hazardous Decomposition Products

Thermal decomposition may yield carbon dioxide and/or carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

No data available

Skin Corrosion/irritation

Non during normal use

No Data available

Serious eye damage/irritation

Germ cell mutagenicity

This product is not classified mutagenic

Carcinogenicity

May cause cancer

Respiratory/Skin Sensitization

Slightly irritating to respiratory system

No data available

Reproductive toxicity

The current toxicological knowledge allows to not classify the product as a toxic to reproduction.

Specific Target Organ Toxicity – Repeated Exposure

No data available

Aspiration hazard

May be fatal if swallowed and enters airways

Specific Target Organ Toxicity – Single Exposure

No data available

12. ECOLOGICAL INFORMATION

Bio-accumulative Potential

No data available

Persistence and Degradability

Readily biodegradable (74% after 28 days).

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste from Residues / Unused Products

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

California Hazardous Waste Codes 331

(Non-household setting)

14. TRANSPORT INFORMATION

DOT Not regulated
IMDG Not regulated
IATA Not regulated

U.S. Federal Regulations

15. REGULATORY INFORMATION

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	SARA 313 - Threshold Values %
MINERAL SEAL OIL	0064742-46-7	85-100%

16. OTHER INFORMATION

General

TCMP urges each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. It is the Buyer's/User's responsibility to ensure that his activities comply with all Federal, State, Provincial or Local laws. The information presented here pertains only to the product as shipped. The information contained herein is based on our current knowledge of the underlying data and is intended to describe the product for the purpose of health, safety and environmental requirements only. No warranty or guarantee is expressed or implied regarding the accuracy of this data or the results to be obtained from the use of the product.

HMIS

Health	/	1
Flammability		1
Physical hazard		0
Personal protection		X

(*) – Chronic effects

Caution: HMIS ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

Issuing Date: 29-OCT-2019
Revision Date: 5-NOV-2019

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of SDS